

► Our technology. Your success.
Pumps ■ Valves ■ Service



PERIBOOST Mini booster Pumps



PERIBOOST

Mini booster pumps

Applications

- For Pressurised water, showers in bathroom.

Features

- Light weight and compact design.
- Pressure system is designed so as to automatically start the pump when system cut in pressure reaches 1.1 bar and stops when cut off pressure reaches to 1.8 bar.
- Motor fitted with thermal overload protector.
- Wear resistant shaft and impeller.
- 2 Litre pressure tank with special rubber bladder and pressure switch.

Standard Specifications

- Pump Size : 25 x 25 mm
- Capacity : up to 2000 LPH
- Total Head : up to 24 meters
- Power : 0.37 kW (0.5 HP)
- Voltage Band : 180-240 V
- Temperature : Suitable up to 65° C water
- Liquid : Clear Water



Pump Model	kW (HP)	Starting method	Pipe Size (mm)	Weight approx. (kg)	Total Head in Metres							
					6	9	12	15	16.5	18	21	24
					Discharge in LPH							
Periboost 05	0.37/0.5	CSR	25 X 25	7.5	2000	1750	1500	1200	1100	950	700	400



KSB Pumps Limited
Standard Pumps Division
 Plot No. E-3 & E-4, MIDC Sinnar, Nashik - 422 113.
 Tel.: +91-2551-230252 / 53, 229700 Fax : +91-2551-230254 www.ksbindia.co.in